

PizzaMaster® 550 series

Technical Specifications – Order Form

Make your choice

☐ PM 551ED
☐ PM 552ED

☐ PM 551ED-1
☐ PM 552ED-1

☐ PM 552ED-2

PizzaMaster_550series_Technical Specifications 90004_EN_R1C

Multi Purpose CounterTop ovens

COMPACT, versatile and high efficient – stone hearth ovens



- 80 Different Sizes
Including Modular and CounterTop ovens
- High Power
- High Temperature
- Special Clay Hearthstone
- Unique Scandinavian Design
- “Extra” is Standard
- Smart Unique Options
- International Certificates

External and Inside dimensions per deck for models

Internal dimensions per deck: depth = 535 mm/21.1 in, width = 535 mm/21.1 in



Standard equipment

- Dual halogen lighting in each deck
- Hearth of natural material with crisping function
- Stainless steel exterior
Except of exterior bottom and backside
- Turbo start function
- Indicators for thermostat, turbo-start and service
- See-through oven door with heat-reflecting glass
- 400°C / 752°F as standard
- Digital Display
- Timer with manual shut-off alarm
- Auto-Timer with alarm
- Stackable
Optional stacking kit is required

Mandatory fields

Electrical connection

- ☐ 230V 1ph
- ☐ 230V 3ph
- ☐ 400V 3ph+N
- ☐ 200V 3ph
- ☐ 208V 1ph
- ☐ 208V 3ph
- ☐ 240V 1ph
- ☐ 240V 3ph
- ☐ 480V 3ph+N
- ☐ 400V 3ph
- ☐ 460V 3ph

Optional equipment

Make your choice

- ☐ Marine model
- ☐ Stacking kit
required when stacking ovens

High temperature deck*

500°C / 932°F

- ☐ Deck 1 (lower)
- ☐ Deck 2

**Not in combination with steam system*

PizzaMaster design solution

- ☐ Phantom Black
- ☐ Royal Gold

Steam system*

- ☐ Deck 1 (lower)
- ☐ Deck 2

**Not in combination with high temperature deck and/or oven deck with 2 stones per deck. Add oven depth with 100 mm / 4 in.*

Support

- ☐ PM 551-S
any 551 model
- ☐ PM 552-S
any 552 model
- ☐ PM 553-S
any combination of 551 + 552 models stacked
- ☐ PM 554-S
any combination of 552 + 552 models stacked

Shelf support package*

- ☐ SP-1
for support 551-S
- ☐ SP-2
for support 552-S

**shelf support package is ordered separately, nor is it available for supports 553 and 554.*

Approvals available



**2 YEAR
WARRANTY**

Limited

PizzaMaster®



Customer Support: Tel: +46 33 230-025

E-mail: info@pizzamaster.com

Website: www.pizzamaster.com

BakePartner has a policy of continuous product development and reserves the right to change specifications and designs without prior notice.

PizzaMaster® 550 series

Technical Specifications – Installation Guide

PM 551ED
PM 552ED

PM 551ED-1
PM 552ED-1

PM 552ED-2

PizzaMaster_550series_Technical Specifications 90004_EN_R1C

PizzaMaster® CounterTop 550 series

Model	Dimensions in millimetres Width x Depth x Height		Dimensions in inches Width x Depth x Height		Separate decks per oven	Hearth- stones per oven	Power kW	Weight Kg / lb	
	External	Internal (per hearthstone)	External	Internal (per hearthstone)					
PM 551ED	775 x	535 x 535	30.5 x 28.5 x 19.7	x 195 (1 pcs)	1	1	4.41	90/198	
PM 551ED -1	725 x500			x 85 (2 pcs)		x 3.4 (2 pcs)	2	5.59	101/223
PM 552ED	775 x 725 x800		x 195 (2 pcs)	21.1 x 21.1	2	3	8.77	146/322	
PM 552ED -1			x 195 (1 pcs)	30.5 x 28.5 x 31.5		x 7.7 (1 pcs)	4	10.95	157/346
PM 552ED -2			x 85 (2 pcs)			x 3.4 (2 pcs)		13.13	168/370
				x 85 (4 pcs)					

Support 550 series

Model	Dimensions in millimetres Width x Depth x Height	Dimensions in inches Width x Depth x Height	Shelf support package (option)	No. of shelf possible to stack per package	Weight Kg / lb
PM 551-S	775 x 723	x 900	SP-1	4	17/37
PM 552-S		x 750	SP-2	4	16/35
PM 553-S		x 450	-	-	15/33
PM 554-S		x 300	-	-	14/31

IMPORTANT!

All installations and services must comply to local and national codes and be carried out by qualified servicers and electricians only.

Placement

Oven must be installed with a clearance of 50 mm / 2 in towards all sides.

Electrical

For wire dimension (mm²/AWG) see ovens connecting terminal and/or the manual.


Ventilation

No ventilation connection required

Water

Pressure between 1-6 bar (0.1-0.6 MPa). Connection G ¾ " / NH ¾ " (for US/CAN).

Connections



Amps per phase and per Oven (models with 2 numbers require 2 separate electrical supplies)

Model	230V 1ph+N	230V 3ph	400V 3ph+N	200V 3ph	208V 1ph	208V 3ph	240V 1ph	240V 3ph	480V 3ph+N	400V 3ph	460V 3ph (440-480)
PM 551ED	19.2	-	-	17.7	21.2	-	20.0	-	-	-	-
PM 551ED-1	28.7	16.7	9.7	17.7	31.7	18.4	29.9	17.4	8.1	9.6	8.3
PM 552ED	38.4	25.0	19.4	26.7	-	27.7	-	26.1	16.1	14.4	12.5
PM 552ED-1	-	33.3	19.4	35.4	-	36.8	-	34.7	16.1	19.1	16.7
PM 552ED-2	-	33.3	19.4	35.4	-	36.8	-	34.7	16.1	19.1	16.7

Distributor

Built for Extreme Temperature



Support:
PM 551-S

Ovens:
1 deck model



Support:
PM 552-S

Ovens:
2 deck model



Support:
PM 553-S

Ovens:
2 deck + 1 deck
models stacked



Support:
PM 554-S

Ovens:
2 deck + 2 deck
models stacked

Stacked ovens require optional stacking kit



PizzaMaster®

Customer Support: Tel: +46 33 230-025

E-mail: info@pizzamaster.com

Website: www.pizzamaster.com

